

The NIOSH approval label will be printed on the carton.

**JFY6151 NIOSH
N95 Particulate Respirator
With exhalation valve**

User's Instruction Manual

**JFY INDUSTRIAL CO., LTD.
8F-, No. 159, Sec. 1, Hsin Tai Wu Rd. His-Chih, Taipei Hsien,
Taiwan**



**N95: 95% filter efficiency level,
Effective against particulate aerosol
free of oil**

**ATTENTION: READ APPLICATIONS, LIMITATIONS
AND FITTING INSTRUCTIONS ON BOX BEFORE
RESPIRATOR IS WORN.**

CONTENTS: 12 Respirators

APPLICATIONS

USE AGAINST:

NIOSH approved for protection against particulate aerosols free of oils.

JFY recommends this respirator for use against particulates such as flour, iron coal and minerals.

DO NOT USE AGAINST:

1. Vapors, paint spray, oil-based aerosols, asbestos and sand blasting.
2. Any contaminant whose concentration is unknown, or immediately dangerous to life.
3. Concentrations of Dust and Mists which exceed the maximum use concentration or 10 times contaminant's permissible exposure limit established by OSHA.

WARNING:

1. These respirators do not supply oxygen. Use only in well ventilated areas containing sufficient oxygen to support life.
2. Leave contaminated area immediately if the respirator becomes damaged and proper fit cannot be obtained or breathing becomes difficult. Dispose and change the respirator.

IMPORTANT LIMITATIONS:

1. All instructions and warnings have to be followed. Failure to do so will reduce the efficiency of respirator and cause sickness or death.
2. Training on the proper use of respirator must be provided by the employer in accordance with the safety and health standard.
3. Do not alter or modify the respirator.
4. Not suitable for persons with beard or other facial hair which may reduce the efficiency of respirator.
5. The use and reuse of this respirator is subject to consideration of hygiene damage and increased breathing resistance. For dirty workplaces, service time should not be extended beyond 8 total hours of use.
6. Avoid direct exposure of sunlight during storage as the filter media in this respirator can degrade by extended exposure to direct sunlight

Instructions for the 6151 N95 Maintenance free respirator


Fitting Instructions

The respirator user must be fit tested according to OSHA regulation 29 CFR 1910.134.

1. Mould the nosepiece to the shape at your fingertips, allowing the headbands to hang below your hand.
2. Press the respirator against your face with the nosepiece on the bridge of your nose.
3. Place the top band high on the back of your head. Move the bottom band over your head and position it below your ears.
4. Using both bands, mould the nosepiece to the shape of your nose.
5. Test the fit. Cup both hands over the respirator and exhale vigorously. If air flows around your nose, tighten the nosepiece. If air leaks around the edges , reposition the bands for better fit.

If you CANNOT achieve a proper fit, DO NOT enter the contaminated area.
See your supervisor for proper fitting respiratory protection.

1.



2.



3.



4.



5.

